

Portable ABC Dry Powder Fire Extinguisher - 10 kg

Model BZ-10 KG ABC P | Stored-pressure portable type | Classes A, B & C



TECHNICAL SPECIFICATIONS

Capacity	10 kg
Extinguishing Agent	ABC Powder - MAP 40%
Fire Rating	43A 233B
Cylinder Material	Mild Steel (M.S)
Expellant	Nitrogen
Operating Pressure	14 bar
Test Pressure	27 bar
Temperature Range	-30 C to +60 C
Minimum Discharge	19 sec
Discharge Range	2 m minimum
Country of Origin	China

APPLICATION Multipurpose ABC dry powder protection for ordinary combustibles, flammable liquids and energized electrical equipment.

OPERATION Aim at the base of the fire, squeeze the lever and sweep side to side. Recharge after any use.

BLITZ ABC DRY POWDER RANGE

Model	Capacity	Fire Rating	Discharge	Pressure
BZ-1 KG ABC P	1 kg	8A 55B	10 sec	14 bar
BZ-2 KG ABC P	2 kg	8A 55B	10 sec	14 bar
BZ-3 KG ABC P	3 kg	2A 34B	19 sec	14 bar
BZ-4.5 KG ABC P	4.5 kg	21A 113B	15 sec	14 bar
BZ-6 KG ABC P	6 kg	34A 233B	19 sec	14 bar
BZ-10 KG ABC P	10 kg	43A 233B	19 sec	14 bar
BZ-25 KG ABC P	25 kg	20A 233B	30 sec	14 bar
BZ-50 KG ABC P	50 kg	20A 233B	30 sec	14 bar

SOURCE AND TRACEABILITY

The exact model image and technical values are taken from the BLITZ Dry Chemical Powder product page published by Rakme Fire Fighting Company.
<https://www.rakmefire.com/product/dry-chemical-powder>