


Fire Alarm Cable 2Cores Shielded 18AWG

Basic Construction

Conductor		2 Cores
	Material	CCA
	AWG	18AWG
Dielectric	Material	Fire Resistance PVC
Drain wire	Material	CCA
Jacket	Material	Fire Resistance PVC
	Nom.Dia(mm)	5.8

NOTE: The Jacket diameter tolerance is $\pm 0.2\text{mm}$



BASIC CHARACTERISTICS

Min insulation resistance 20°C	200 M Ω / km
Temperature Rating	-20°C to 75°C
Operating Voltage	300V
Minimum Bend Radius	8×Diameter
Flammability / Reaction to Fire	IEC/EN 60332-1-2:2005+A1:2016+A11:2016+A12:2021
CPR Compliance	CPR Euroclass: Eca
European Directive Compliance	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2015/863/EU (RoHS 2 amendment)
APAC Compliance:	China RoHS (GB/T 26572-2011)
Quality management system:	ISO 9001:2015



Packing

100m plastic reel



305m wooden drum




Fire Alarm Cable 2Cores Shielded 16AWG

Basic Construction

Conductor		2 Cores
	Material	CCA
	AWG	16AWG
Dielectric	Material	Fire Resistance PVC
Drain wire	Material	CCA
Jacket	Material	Fire Resistance PVC
	Nom.Dia(mm)	6.4

NOTE: The Jacket diameter tolerance is $\pm 0.2\text{mm}$



BASIC CHARACTERISTICS

Min insulation resistance 20°C	200 M Ω / km
Temperature Rating	-20°C to 75°C
Operating Voltage	300V
Minimum Bend Radius	8×Diameter
Flammability / Reaction to Fire	IEC/EN 60332-1-2:2005+A1:2016+A11:2016+A12:2021
CPR Compliance	CPR Euroclass: Eca
European Directive Compliance	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2015/863/EU (RoHS 2 amendment)
APAC Compliance:	China RoHS (GB/T 26572-2011)
Quality management system:	ISO 9001:2015



Packing

100m plastic reel



305m wooden drum

