



MHSF-103-S-E



MHSF-103

TECHINICAL DATA

Manufactured from Steel or Stainless Steel, with thickness of 1mm to 2mm, with all round folded edges, even Hose reel edges are curled to assure the safe handling. Al-Sabeh Fire Hose Cabinet are fabricated with metal inert gas welding process, then pretreated with zinc phosphate to improve rust resistance, afterwards, they are electrostatically painted with red polyester resin paint before being backed in the oven to give a hard wearing resistance and gloss finish.

Fire Hose cabinets are painted red color polyester resin Texture finish.

Fire Hose have been hydrostatically tested to 40 bar pressure for leaks. High level quality control standards are implemented to get quality products.

Standard Features

Provides with two knockouts, which allows either left or right side water entries.

Right hand door leaf hinged flush mounted on door frame, 180 door opening.

For fixing 10 mm dia, holes are provided on the back.

English & Arabic language operating instructions.

White color synthetic Fire Hose 1.5» x 30 meters long, Brass or aluminum NST thread.

1.5» adjustable fog nozzle with NST thread base.

1.5» Landing valve with NST thread Male / Male.

مواصفات الفني

الصندوق مصنوع من الصاج أو الاستنسل استيل بسماكة 1 ملم إلى 2 ملم. يتم طي الأطراف الخارجية البكرة إلى الداخل وذلك من أجل استخدام آمن. الصناديق المصنوعة من الصاج يتم دهانها بالبودرة إلكتروستاتيكية، ثم تعرض الفرن على درجة حرارة تتراوح بين ٦٠ و ٢٠٠ درجة مئوية، مما يكسبها مظهر جذاباً إضافة إلى حمايتها من العوامل الجوية كالصدأ. يتم دهن صناديق خراطيم إطفاء الحريق بدهان الكهراء المطفي باللون الاحمر أو أي لون على حسب اللون المطلوب وهذا الدهان قوي التحمل ومانع للصدأ.

خراطيم إطفاء الحريق قد تم اختباره هايدرلوكيا على ضغط ٤٠ بار مع مراعاة معايير الرقابة على تنفيذها للحصول على منتجات ذات جودة عالية.

الميزات القياسية

يقدم الصندوق مع فتحتين، إما إلى اليسار أو اليمين والتي تسمح المياه من الجانب.

فصالات باب الصندوق من النوع الجيد ويفتح الباب حتى ١٨٠ درجة. يتم عمل اربع ثقب مقاس عشرة ملم لتثبيت صندوق الحريق من الخلف على الحائط.

تعليمات الاستعمال باللغة العربية والانجليزية.

خرطوم من الكتان السميك بقطر ٥٠، بوصة طول ١٠٠ قدم، مصمم خصيصاً لمصنع تحت ماركة (السابح) على ضغط ١٣ بار. يتم تثبيته على بكرة داخل الصندوق بطريقة خاصة لضمان سهولة سحب الخرطوم عند التشغيل.

قاذف قابل الضبط ليعطي قذفاً مستقيماً للماء أو رذاذاً ضبابياً إضافة إلى وضع الإغلاق كما تم تزويده بمحس نحاسي.

صمام نحاس واحد ونصف بوصة ١٦ بار.

Model	SURFACE TYPE			RECESSED TYPE		
	Width	Height	Depth	Width	Height	Depth
MHSF-103	650	650	150	650	650	150
MHSF-103-G	650	650	150	650	650	150
MHSF-103-E	900	650	180	900	650	180
MHSF-103-E-G	900	650	180	900	650	180
MHSF-103-S	650	650	150	650	650	150
MHSF-103-S-G	650	650	150	650	650	150
MHSF-103-S-E	900	650	180	900	650	180
MHSF-103-S-E-G	900	650	180	900	650	180