

Portable CO2



Note:

Model CD5G, CD6G and CD5L are SASO Approved

SFFECO Portable Carbon Dioxide Fire Extinguishers are known for its high reliable performance and ease of handling. The cylinder for CO2 Fire Extinguishers are seamless and extruded from high grade Chrome Molybdenum Steel or Manganese Steel or Carbon Steel.

Carbon Dioxide is discharged as a white cloud of snow which throttles a fire by eliminating the oxygen. Designed to protect areas where class B (flammable liquids and gases) or Electrical class of fires could occur.

Technical Specifications:

- ❖ Extinguishing Agent : CO2
- ❖ Test Pressure : 250 Bar
- ❖ Coating : Electrostatic Polyester Powder
- ❖ Storage Temperature : -20°C to +60°C

Class of Fire:



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.

Model	CD 3-G	CD 5-G	CD 6-G	CD 5-L	CD 10-L
Capacity	3 Kg	5 Kg	6 Kg	2.27 Kg	4.54 Kg
Total Weight	10.5 Kg	16.3 Kg	18.7 Kg	8.45 Kg	15.35 Kg
Total Height (mm)	675	755	790	640	705
Total Width (mm)	175	190	190	170	190
Cylinder Height (mm)	580	600	675	540	600
Cylinder Diameter (mm)	115	145	145	100	145
Hose Length (mm)	Only horn	1220	1220	Only horn	1220
Maximum Effective Range (m)	5	5	5	5	5
Duration of Discharge (Sec)	9-11	9-11	9-11	7-9	9-11